

# NOVA FIBER (S)



**GHSF - 8060**

PLACES OF APPLICATION	DIMENSION
<ul style="list-style-type: none"> <li>Industrial floors</li> <li>Roundabouts &amp; roads</li> <li>Precast concrete</li> <li>Slab on pile</li> </ul>	<ul style="list-style-type: none"> <li>Length: 60 mm ± 7,5%</li> <li>Diameter: 0.75 mm ± 7,5%</li> <li>Aspect ratio (l/d): 80</li> <li>Hooked End / Glued</li> </ul>
PROPERTIES	BENEFITS
<ul style="list-style-type: none"> <li>Tensile strength(Rm):1200±7.5% MPa</li> <li>Young's Modulus: 195+15% GPa</li> <li>Quantity of fibres: 4600 Fiber/kg</li> <li>Minimum Dosage: 12 kg/m<sup>3</sup></li> </ul>	<ul style="list-style-type: none"> <li>Easy to use &amp; high performance</li> <li>Even dispersing throughout concrete</li> <li>Saves the contractor time and money</li> <li>Improves site safety</li> <li>Superior crack control to conventional methods</li> <li>Degradable bag means less handling and wastage</li> </ul>
STORAGE	PACKING
 	 20kg Box  25kg Bag  0.5 ton/ 0.6 ton / 1 ton /1.2 ton Big Bag

**CE**  
1301-CPR-2417  
EN 14889-1

**EACC**  
ISO 9001  
ISO 9001:2015